



# Atrust

## Quad-Display

### Thin Client t226W

Atrust t226W is a Windows Embedded OS based thin client computer. Developed by Atrust, the ACS (Atrust Client Setup) software is also built in to help effective management of t226W. With the support of Citrix® ICA/HDX™, Microsoft® RDP™ with RemoteFX™ and VMware® Horizon View™, t226W can be used to create virtual and session-based desktop experiences from many remote desktop capable operating systems. t226W offers a rich computing experience where applications look, feel, and behave as local devices, including high-definition multimedia content.



#### 1 Power Button

Press to turn on/off the client.

#### 2 Power LED

Lights blue when powered on.

#### 3 Microphone Port

Connects to a microphone.

#### 4 Headphone Port

Connects to a set of headphones or speaker system.

#### 5 USB 2.0 Port x 2

Connects to a USB device.

#### 6 USB 3.2 Gen 1 x 2

Connects to a USB device.

#### 7 USB 3.2 Gen 2 Type C

Connects to a USB device.

#### 8 Kensington Lock Slot

Connects a Kensington cable to secure the thin client.

#### 9 USB 2.0 Port x 2

Connects to a USB device.

#### 10 USB 3.2 Gen 1 x 2

Connects to a USB device.

#### 11 DisplayPort x 4

Connects to a monitor.

#### 12 LAN Port

Connects to a local area network.

#### 13 DC IN

Connects to an AC adaptor.

## Atrust t226W Features

- ▶ Quad display support
- ▶ Simplified management
- ▶ Slim and robust design
- ▶ Low power consumption
- ▶ Lower total cost of ownership (TCO)
- ▶ Supported Protocols  
t226W supports the following protocols:  
Citrix® ICA/HDX™, Microsoft® RDP™ with RemoteFX™, VMware® Horizon View™

# Atrust t226W

<b>System</b>	
Processor	Intel® Tiger Lake i3-1115G4, 3.0GHz (Max Turbo 4.10 GHz)
<b>Memory</b>	
System memory	4GB (Manufacturing option : 8GB/16GB/32GB/64GB)
Flash memory	64GB (Manufacturing option : 128GB/256GB/512GB)
<b>Graphics</b>	
Maximum resolutions	DisplayPort up to 4096 x 2160 @60Hz
<b>I/O Interfaces</b>	
I/O ports	Front: 2 x USB 2.0, 2 x USB 3.2 Gen 1, 1 x USB 3.2 Gen 2 Type C, 1 x Microphone Port, 1 x Headphone Port, Rear: 4 x DisplayPort, 2 x USB 2.0, 2 x USB 3.2 Gen 1, 1 x RJ-45, 1 x DC IN
<b>Networking</b>	
Ethernet	10Mb/100Mb/1Gb/2.5Gb
WiFi(Optional)	IEEE 802.11ac
<b>Dimensions / Weight</b>	
Dimensions	(W) 45.6 x (D) 189 x (H) 204 mm
Weight	1.2 Kg with stand (approximate)
<b>Environment</b>	
Operating temperature	0°C ~ 35°C
Non-operating temperature	-20°C ~ 60°C
Operating humidity (Rh)	10% ~ 90% (non-condensing)
Non-operating humidity (Rh)	5% ~ 95% (non-condensing)
<b>AC Adaptor</b>	
Maximum Output Power	AC adaptor 90W
<b>Software</b>	
Operating system	Windows®10 IoT Enterprise 2019 LTSC
Management	Atrust Device Manager (ADM) / Atrust Client Setup (ACS)
Protocols	Citrix® ICA/HDX™, Microsoft® RDP™ with RemoteFX™, VMware® Horizon View™ (PCoIP/RDP/Blast)
<b>Manufacturing options</b>	Smart Card Reader 2 x COM Port 2nd Lan(2.5Gb)

© 2021 Atrust Computer Corp. The information contained herein is subject to change without notice. Atrust shall not be liable for technical or editorial errors or omissions contained herein. Microsoft and Windows are trademarks of the Microsoft group of companies. Citrix and ICA/HDX are trademarks of Citrix Systems, Inc.. VMware and Horizon View are trademarks of VMware, Inc.. To learn more, visit [www.Atrustcorp.com](http://www.Atrustcorp.com).